

SPECIFICATIONS

Product Description: **FULL MASK LOW PRESSURE SYSTEMS**
 Part Number: **9200 AND 9210 SERIES**
 Style: **SUPPLIED AIR**

GENERAL DESCRIPTION:

Our complete Full Mask Low Pressure Systems offer portable and lightweight air sources for one, two, or three workers. They're offered with one, two, or three comfortable full mask supplied air respirators, a ¼ hp, ¾ hp or 1½ hp breathing air pump and a 50' or 100' (15.24 m to 34.4 m) breathing air hose.



FULL MASK RESPIRATOR:

- Durable silicone rubber
- Hypoallergenic and chemical/Ozone resistant
- Replaceable polycarbonate lens
- Removable hairnet
- Down tube comes with a 90-degree elbow that allows it to be directed over the shoulder
 - OBAC quick-connect plug with wide diameter and minimal air restriction

PUMP:

Type: Oil-less, rotary vane
 Vanes: Carbon construction
 Inlet Filter: 40.0 Micron bronze/steel (¼ hp)
 50 Micron felt material with metal grid inlet filter housing
 Exhaust Filter: 0.3 Micron HEPA
 Pressure Gauge: 1½" (3.8 cm) face, steel housing (0-15 psi) (0-1.03 bar)
 Working Pressure: 2-12 psi (0.14-0.83 bar) (15 psi max) (1.03 bar max)
 Performance: 0-5 CFM (0-8.5 m³/hr) (¼ hp)
 0-10 CFM (0-16.99 m³/hr) (¾ hp)
 0-20 CFM (0-33.98 m³/hr) (1½ hp)

MOTOR:

Type: ¼ hp, ¾ hp, or 1½ hp UL Listed
 Volts: 115V/230V AC, Single Phase
 Power Required: 5.5A (1/4 hp), 8.3A (3/4 hp), 16A (1½ hp)

HOSE:

- Polyvinyl chloride with reinforced braided polyester yarn
- -20° F to 150° F (-28.8° C to 65.5° C)
- Maximum pressure 185 psi @ 70° F (12.76 bar @ 21.1° C)

AVAILABLE:

Part Number	Description
9200-01	One Worker Full Mask System with ¼ hp pump & 50' hose (15.24 m)
9200-02	Two Worker Full Mask System with ¾ hp pump & 50' hose (15.24 m)
9200-03	Three Worker Full Mask System with 1½ hp pump & 50' hose (15.24 m)
9210-01	One Worker Full Mask System with ¼ hp pump & 100' hose (34.4 m)
9210-02	Two Worker Full Mask System with ¾ hp pump & 100' hose (34.4 m)
9210-03	Three Worker Full Mask System with 1½ hp pump & 100' hose (34.4 m)